





| 1. | ACCOUNT INF | ORMATION | | | | | | | | | | |
|------|-----------------------------|---|---------------|-----------------|--------|--|----------------|--|--|--|--|--|
| P.O | P.O. # or Quote: | | | | | | | | | | | |
| Dea | ler Contact Name: | | | | | | 1 | | | | | |
| Em | ail Address: | | | | | | | | | | | |
| Pho | one Number: | Fax No | umber: | | | | | | | | | |
| Bill | to (Name): | | | | | | Ш | | | | | |
| Bill | to (Location): | | | | | | | | | | | |
| Shi | p to (Name): | | | | | | | | | | | |
| Add | dress: | | | | | | | | | | | |
| City | | | | | | | | | | | | |
| | vince: | | Code: | | | | | | | | | |
| | er Name or Numb | er: | | | | | | | | | | |
| | er Weight: | | | | | | | | | | | |
| | er Height:at Cushion Thicki | | | | | | | | | | | |
| | | | Diabte | | | 33 | | | | | | |
| KII | ee to Heel Length | i. Leit. | xigiit | | | | | | | | | |
| TH | IE ORDER CAN | NOT BE PROCESSED WITHOU | T THE FO | LLOWING: | | | | | | | | |
| | | er, the client's measurements and wei er errors on the order form. | ight - Amylic | or is not respo | onsibl | e for configuration or size discrepand | ies | | | | | |
| - O | rder confirmations | will be provided by Amylior summarizi | ng the items | s selected. Pl | ease r | review this carefully. | | | | | | |
| - O | nce the order is shi | pped, any changes are subject to the r | eturns polic | y and may be | e proh | ibited. | | | | | | |
| | *IN RED | SHOWS THE ADDITION OF NEW OPT | IONS, UPGF | RADES, PRIC | ING M | ODIFICATIONS OR ADDED NOTES | | | | | | |
| 2. | STANDARD OF | PTIONS | | | | | | | | | | |
| | | e, 6-wheel independent wheel suspensi ' front casters, and standard auto style | | | | | | | | | | |
| 3. | ALLTRACK M | 3 POWER WHEELCHAIR | | | | | | | | | | |
| | ATM3 | ALLTRACK M3 Power Wheelchair | | | | | \$8,020 | | | | | |
| 3.5 | OWNER'S MAI | NUAL | | | | | | | | | | |
| | SOOMATENG | English / Anglais | N/C | SOOMA | TFR | Français / French | N/C | | | | | |
| 4. | USER WEIGHT | PACKAGES | | | | | | | | | | |
| | WCA25 250 lb | Maximum user weight capacity | STD | WCA3 | 300 | lb Maximum user weight capacity | STD | | | | | |
| 5. | STANDARD CO | OLORS | | | | | | | | | | |
| | SCMOBM | Onyx Black Matte | N/C | SCMCA | В | Cabernet | N/C | | | | | |
| | SCMCTB | Cobalt Blue | N/C | SCMBG | М | Bubble Gum Metallic | N/C | | | | | |
| | SCMIOB | Indigo Blue | N/C | SCMHA | В | Habanero Metallic | N/C | | | | | |
| | SCMCRE | Candy Red | N/C | SCMLIM | | SubLime | N/C | | | | | |
| • | OPTIONAL COL | | | | | | · - | | | | | |
| | FCHDD-M | Desert Digital Camo HydroGraphio | cs. | | | | \$795 | | | | | |
| | FCHCF-M | Carbon fiber HydroGraphics | | | | | \$795 | | | | | |
| | FCHWL-M | Woodland Camo HydroGraphics | | | | | \$795 | | | | | |
| | | | | | | | Ψ, σσ | | | | | |







| 5.5 | WHEEL INS | SERT COLORS | | | | | | |
|----------|---|--|--------------|-----------------------|---|----------|--|--|
| | SCCTB-WI | Cobalt Blue | N/C | SCHAB-WI | Habanero Metallic | N/C | | |
| | SCIOB-WI | Indigo Blue | N/C | SCLIM-WI | SubLime | N/C | | |
| | SCCRE-WI | Candy Red | N/C | SCBGM-WI | Bubble Gum Metallic | N/C | | |
| | SCCAB-WI | Cabernet | N/C | 0020m tm | Dazzie Gain Metallie | 14,0 | | |
| _ | _ | colors are not compatible with optional Hy | | colors (ECHDD) F | CHWI and FCHCF) | | | |
| _ | | colors are not compatible with the optiona | • . | • • | , | | | |
| A | Wheel inserts are not available in Onyx Black Matte | | | | | | | |
| 7. | TRANSPORT OPTION | | | | | | | |
| | TTD4 | Tie-down attachment points compliant | t with ISO 7 | 176-19. See own | er's manual for additional details | STD | | |
| 8. | MOTOR PA | CKAGE | | | | | | |
| | MP65B | 6.5MPH 4-Pole Motor Package / with | Brake Rele | ase | | STD | | |
| A | Not compatible | e with the Smart-Track Assistive Driving I | Package opt | ion (SMARTT) | | | | |
| | MP65-OPT | 6.5MPH 4-Pole Motor MP65-OPT Page | kage / with | COG Release | | \$395 | | |
| A | Not compatible | e with the narrow base configuration (FS2 | 2221B) | | | | | |
| 9. | ASSISTIVE DRIVING PACKAGE | | | | | | | |
| | SMARTT Smart-Track Assistive Driving Package \$ | | | | | | | |
| • | | echnology provides increased tracking ca hand function or switch control. | pabilities w | ith enhanced tract | ion and steering precision. This is ideal t | or those | | |
| A | Requires the F | R-net PM 120 Amp Expandable Controller | (ECR120). | | | | | |
| A | This option re | quires the MP65-OPT motor package. | | | | | | |
| A | Not compatible | e with the narrow base configuration (FS2 | 2221B) | | | | | |
| A | Recommende | d for non-proportional Drive Controls | | | | | | |
| 10. | BATTERY O | CHARGER | | | | | | |
| | ВСОВ | 8A Offboard Battery Charger | | | | N/C | | |
| 11. | BATTERY T | RAY AND BASE WIDTH | | | | | | |
| | FS2221B | N2221 - Battery Tray for Group 22 Ba | tteries with | a Narrow 21" bas | se width (Total base width = 21") | N/C | | |
| • | NOT AVAILAB | LE WITH THE FOLLOWING OPTIONS: | | | | | | |
| A | 6.5MPH 4-Pole | Motor Package / with COG Release option | n (MP65-OF | (די | | | | |
| A | Smart-Track o | ption (SMARTT) | | | | | | |
| A | | rs (FC8PTM and FC8PIM) | | | | | | |
| A | 14" x 4" Extra Wide Cast Wheels, Pneumatic Tires (DW144PT and DW144PI) | | | | | | | |
| _ | | | | | | | | |
| | FS22B Battery Tray for Group 22NF Batteries – (Total base width = 23 3/8") | | | | | | | |
| | FS2424B N2424 - Battery Tray for Group 24 Batteries with a Narrow 24" base width (Total base width = 24") N/C | | | | | | | |
| A | | ngle is reduced from 90° to 85° for some s | | | I with the narrow base configuration (FS2 | | | |
| | FS24B | Battery Tray for Group 24 Batteries – | (lotal base | width = $25 \ 3/8"$) | | N/C | | |







| 12 | . BATTERIES | - RE | QUIRES A | SELEC. | TION | | | | |
|----------------|---|----------------------------------|---|--------------|-------------|-------------------|---|---|-------|
| | BAT22NFGEL | Prer | nium CG Pow | er - GEL | Battery | – Group | 22NF – 50 Amps (Each) | | \$335 |
| | BAT24GEL | Prer | nium CG Pow | er - GEL | Battery | – Group | 24 – 70 Amps (Each) | | \$465 |
| | ВАТО | Omi | ssion of the b | atteries | | | | | N/C |
| 14 | . DRIVE WHE | EL | | | | | | | |
| | DW14PT | 14" (| Cast Wheel P | neumatio | c Tires | | | | STD |
| | DW14PI | 14" (| Cast Wheel P | neumatio | c with Fo | am Filled | d Tires | | N/C |
| | DW144PT | 14" : | x 4" Extra Wic | de Cast V | Vheels, F | Pneumati | c Tires | | \$200 |
| | DW144PI | 14" : | x 4" Extra Wio | de Cast V | Vheels, F | Pneumati | c with Foam Filled Tires | | \$595 |
| | | A | Increases the | e overall | width of t | he base l | oy 2 ¾" | | |
| | | A | Not compatil | ole with t | he narrow | base co | nfiguration (FS2221B) | | |
| | DW12PT | 12 ½ | ½" Cast Whee | l Pneum | atic Tires | | | | N/C |
| | DW12PI | 12 ½ | ∕₂" Cast Whee | l Pneum | atic with l | Foam Fil | led Tires | | N/C |
| | | • | 12 ½" Drive v | | duce ove | rall seat t | to floor height by ¾", lowers ground | clearance and speed, but incr | eases |
| 15 | . FRONT CAS | STER | lS | | | | | | |
| | FC6S | 6" S | olid Casters – | · (Not ava | ailable wi | th the 14 | " x 4" Extra Wide Cast Wheel option | ns DW144PT or DW144PI) | STD |
| | FC8PTM | | neumatic Cas | | | | - 1 | , | N/C |
| | FC8PIM | 8" P | neumatic Cas | sters with | Foam Fi | illed Tires | S | | N/C |
| | | A | The 8" caste | rs are NO | T compa | tible with | the 12 1/2" Drive wheel configuration | (DW12PT and DW12PI) | |
| | | A | Not compatil | ole with th | he narrow | base co | nfiguration (FS2221B) | | |
| 16 | . SEAT TO FI | OOF | R HEIGHT (I | MEASU | REMEN | т то тн | HE TOP OF SEAT PAN ± 1/4") | | |
| | ► YELLOW | / BOX | ES REPRESE | NT OPTI | ONS THA | T CAN C | ONLY BE SELECTED WITH 12 ½" DI | RIVE WHEELS (SECTION 14) | |
| SE | EAT TO FLOOR | HEI | GHT TABLE | NO PO | WER OF | TIONS 6° | TILT <u>OR</u> ELEVATE (WITH OR WITHOUT RECLINE) | TILT <u>AND</u> ELEVATE (WITH OR WITHOUT REC | |
| ST | FH1550 (15.50 | " STF | :Ш\ | | | | | • | |
| | • | STFH1550 (15.50" STFH) | | | | | | | |
| | FH1650 (16.50 | " STF | | | | | | | |
| ST | FH1650 (16.50 FH1750 (17.50 | | H) | | | | | | |
| | • | " STF | H) | | | | | | |
| ST | FH1750 (17.50 | " STF | H) H) H) | | | | | | |
| ST | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 | " STF " STF " STF | H) H) H) | PECIFI | CATION | (IF NO | T STANDARD) | | |
| ST | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 | "STF "STF "STF | CH) CH) CH) CH) CH) CH) CH) CH) | | | | T STANDARD) ndard. It's not possible to lower the | seat to floor height below | RFQ |
| ST | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 | "STF "STF "STF | CH) CH) CH) CH) CH) CH) CHS CHIGHT S Cific seat to flo | oor heigh | it higher t | than star | ndard. It's not possible to lower the | seat to floor height below | |
| ST ST 17 | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 | "STF"STF | H) H) H) KH) KHEIGHT S Cific seat to flomum ranges. Required at: | oor heigh | it higher t | than star | ndard. It's not possible to lower the | seat to floor height below | |
| ST ST 17 | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 . SEAT TO FI SOMHSS | "STF "STF OOF Speemini | H) H) H) H) KHEIGHT S Cific seat to flomum ranges. Required at: | oor heigh | t higher t | than star | ndard. It's not possible to lower the | · | |
| ST ST 17 | FH1750 (17.50 FH1850 (18.50 FH1950 (19.50 . SEAT TO FI SOMHSS | "STF "STF OOF Specimini A EAT I | H) H) H) H) H) High High High High High High High High | GLE ame seat | it higher t | than star " (± | ndard. It's not possible to lower the | | RFQ |







| 19. | LIGHTING F | PACKAGE | | | | | | | |
|----------|---|--|---------|--|--|--|--|--|--|
| | EOLP | LED Light Package – (Includes front and rear lights with integrated flashers) | \$1,425 | | | | | | |
| A | Requires the u | pgraded Joystick with Light Operation or the OMNI 2 (ECVJ6KL, ECELJL, ECRJCL, ECRJC35B or EDIB). | | | | | | | |
| 20. | NON-EXPAI | NDABLE ELECTRONICS - PG DRIVES VR2 CONTROLLER AND JOYSTICKS | | | | | | | |
| • | VR2 Electronics can only accommodate specific power seat functions and combinations such as Tilt / Elevate / Recline / Power Cent Mount / Combined Power Legs / Tilt + Power Center Mount / Tilt + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Tilt + Elevate (Custom) | | | | | | | | |
| | ECV902A | VR2 90 Amp Drive Controller – (Requires the selection of VR2 joystick below) | STD | | | | | | |
| | ECVJ4K | VR2 Standard 4-Key Joystick | STD | | | | | | |
| | ECVJ6K | VR2 6-Key Joystick (Allows for single or select dual power options to operate through this joystick) | N/C | | | | | | |
| | ECVJ9KL | VR2 9-Key Joystick with Lighting Operation (Allows for single or select dual power options to operate through this joystick) | \$150 | | | | | | |
| 21. | EXPANDAB | LE ELECTRONICS - PG DRIVES R-NET CONTROLLERS | | | | | | | |
| | ECEL90 | R-net EL 90 Amp Expandable Controller | \$175 | | | | | | |
| | ECR120 | R-net PM 120 Amp Expandable Controller | \$275 | | | | | | |
| 22. | EXPANDAB | LE ELECTRONICS - PG DRIVES R-NET JOYSTICKS | | | | | | | |
| • | SELECTION C | OF ONE JOYSTICK OPTION BELOW IS REQUIRED WITH THE EXPANDABLE CONTROLLER ECEL90 OR ECR | 120 | | | | | | |
| | ECO | Omit Joystick – (For use with an Omni 2 Display) | N/C | | | | | | |
| | ECELJ | R-net - (LED) – Joystick | STD | | | | | | |
| | | ▲ This joystick is not compatible with the Memory Seat Program Option (SACMEMORY and MACMEMORY) | | | | | | | |
| | ECRJC | R-net Joystick with Color screen | \$155 | | | | | | |
| • | JOYSTICKS W | ITH LIGHTING OPERATION | | | | | | | |
| | ECELJL | R-net – (LED) – Joystick with Lighting Operation | \$125 | | | | | | |
| | | ▲ This joystick is not compatible with the Memory Seat Program Option (SACMEMORY and MACMEMORY) | | | | | | | |
| | ECRJCL | R-net Joystick with Color screen and Lighting Operation | \$180 | | | | | | |
| • | ADVANCED JO | DYSTICK | | | | | | | |
| | ECRJC35B | R-net Advanced Bluetooth Joystick (3.5" Screen). Lighting Operation, paddle switches, shortcut keys and stereo jacks | \$1,105 | | | | | | |
| 23. | JOYSTICK | MOUNT | | | | | | | |
| | JSMF | Fixed Joystick Mount | N/C | | | | | | |
| | JSMSA | Swing Away Joystick Mount – Height adjustable, Angle adjustable and Multi-Axis | \$235 | | | | | | |
| | Select: | Set-up with standard installation to swing-away sideways | | | | | | | |
| | | Set-up at 35° to swing-away sideways and downwards | | | | | | | |
| | | Set-up at 35° angle may cause interference with the user's limbs when the new Signature cantilever armre (SOAFBxxx) is internally rotated. | est | | | | | | |
| | JSMCM | Bodypoint Tri-Lock Midline Mounted Swing Away Joystick Mount | \$275 | | | | | | |
| 24. | JOYSTICK | MOUNT SUPPORT | | | | | | | |
| | JSMFH | Joystick mount support Bracket | STD | | | | | | |
| 25. | JOYSTICK | HAND MOUNT | | | | | | | |
| | HML | Install Joystick on Left hand side HMR Install Joystick on Right hand side | | | | | | | |
| | | | | | | | | | |









| 26. JOYSTICK | HANDLE | | | | | | | | | |
|---------------|--|-----------------|---------------|--------------------------------------|----------------|--|--|--|--|--|
| JSH | Standard Joystick Gimble | STD | JBAT | Stick Handle 3" in Length | \$130 | | | | | |
| JBH | Ball Handle | \$85 | JFBH | Foam Ball Handle | \$70 | | | | | |
| JTH | T-Handle | \$155 | JMUSH | Bodypoint Mushroom Handle | \$210 | | | | | |
| JGP | Bodypoint 4" U-shaped Handle | \$210 | | | | | | | | |
| 27. ATTENDAN | 27. ATTENDANT DRIVE CONTROL OPTION | | | | | | | | | |
| EADC | Attendant Hand Control | | | | \$1,150 | | | | | |
| 28. ATTENDAN | IT JOYSTICK HAND MOUNT | | | | | | | | | |
| EADCL | Install Attendant Joystick on Rear Left | hand side | EADCR | Install Attendant Joystick on Rear R | ight hand side | | | | | |
| 29. R-NET OMN | II 2 - ENHANCED DISPLAY & DIGI | TAL INTERF | ACE BOX | (REQUIRED WITH SPECIALTY O | ONTROLS) | | | | | |
| EDIB | Omni 2 – (Enhanced Display & Digita | al Interface Bo | x with Blueto | ooth and Infrared) | \$1,915 | | | | | |
| | Allows the switch operation of alternative devices through driver controls. Requires the R-net fully Expands Controller (ECR120) | | | | | | | | | |
| | ▲ The Omni 2 display mount must be selected from the option below. | | | | | | | | | |
| 30. OMNI 2 EN | 30. OMNI 2 ENHANCED DISPLAY MOUNT | | | | | | | | | |
| EDSAM | DSAM User Swing Away Mount | | | | | | | | | |
| | EDML – (Install Display on LH | side) E | DMR - (Ins | stall Display on RH side) | | | | | | |
| 31. ENVIRONM | ENTAL CONTROL MODULE | | | | | | | | | |
| ECU | Environment control module – (Output | ut Module) | | | \$995 | | | | | |
| | ▲ Requires one of the fully expan | dable R-net coi | ntrollers (EC | EL90 or ECR120). | | | | | | |
| 33. SIGNATUR | E TAILORED POWER POSITIONI | NG SOLUTIO | ONS / REH | AB SEAT | | | | | | |
| SAABA | Signature Rehab Seat – (Seat Fra | ame only) | | | \$880 | | | | | |
| SAPTX | Signature CG Power Tilt | | | | \$6,195 | | | | | |
| | ▲ This option includes the Signa | ture Rehab Sea | nt – (SAABA) | | | | | | | |
| SAPRX | Signature 165° Power Recline wit | h Mechanical | Shear Redu | ction (MSR) | \$7,845 | | | | | |
| | ▲ This option includes the Signa | ture Rehab Sea | nt – (SAABA) | | | | | | | |
| SAPTPRX | Signature CG Power Tilt and 165° | Power Reclin | e with Mech | nanical Shear Reduction (MSR) | \$11,495 | | | | | |
| | ▲ This option includes the Signa | ture Rehab Sea | nt – (SAABA) | | | | | | | |
| SAPESX | ALTA 11" Power Seat Elevation | | | | \$4,495 | | | | | |
| ADDDESS | ▲ This option includes the Signa | | , , | | #0.40 = | | | | | |
| ADDPESX | Module – Add ALTA 11" Power Se | | | | \$2,495 | | | | | |
| ADDMR | Module – Manual Recline with Me | | | , , | \$1,125 | | | | | |
| | ▲ The maximum user weight cap | acity with this | option is 250 | ID. | | | | | | |







| 34. | ELECTRON | ICS - SINGLE | (1 ACTUATO | R) POV | VER SEAT | FUNCTION | N CONTROLLER | | |
|-------------|-----------------|------------------------|----------------------------------|------------------------|--------------------------------|----------------------|-------------------------|--------------------------|---------|
| > | SINGLE SEAT F | UNCTION USING | AN EXTERNAL | TOGGLE | OR OPTIONA | L SWITCH ON | ILY (For both expandab | le and non-expandable sy | stems) |
| | SOLO | Single function | controller (Incl | udes an | external tog | gle switch) | | | STD |
| • | OPTIONAL SW | TTCHES | | | | | | | |
| | SWTOGGLE | Single Toggle S | witch | | | | | Attendant Activation | \$100 |
| | SWPUSH1 | Single Push Bu | tton Switch – (| Single M | lode: SAC) | | User Activation | Attendant Activation | \$90 |
| | SWPUSH2 | Dual Push Butte | on Switch – (D | ual Mode | e: SAC) | | User Activation | Attendant Activation | \$180 |
| | SSBS | Buddy Button Switch | Black | Red | Green | Yellow | User Activation | Attendant Activation | \$230 |
| | SSES | Egg Switch-Bla | ck | | | | User Activation | Attendant Activation | \$116 |
| | SSML | Ultra Light Swit | ch | | | | User Activation | Attendant Activation | \$295 |
| • | SINGLE SEAT | FUNCTION THRO | | NTROL | | | | | |
| | EPSV | Single Function | Through VR2 | Non-Exp | pandable Dri | ve Control | | | N/C |
| | | ▲ Allows for | activation of a | single po | wer option th | rough VR2 c | controller | | |
| | | ▲ Does not a | llow for control | of powe | r option thro | ıgh drive coı | ntrol and separate swit | ches | |
| | | Control of addition to | | ation wit | th tilt is availa | able as a cus | tom. Check appropria | te box in custom section | 72 in |
| | | VR2 Electro | onics can only I Power Legs / | accommo Tilt + Elev | odate specific vate (Custom | c power seat) | functions such as Tilt | / Recline / Power Center | Mount |
| | | ▲ Choose EF | SV2 to operate | select po | ower combina | ations | | | |
| | EPSEL | Single Function | Through Drive | e Control | I with R-net 9 | 0-amp cont | roller | | N/C |
| | | ▲ Allows for | activation of si | ngle pow | er option thro | ough R-net 9 | 0-amp controller | | |
| | | ▲ Compatible | with all R-net | joysticks | • | | | | |
| | | ▲ Does not a | llow for control | of powe | r option throu | ıgh drive coı | ntrol and separate swit | ches | |
| | | ▲ Can not op | erate more tha | n one po | wer option | | | | |
| | | ▲ If selecting | memory seatii | ng, choos | se SAC below | • | | | |
| | | ▲ If selecting | 120-amp R-ne | controll | er, choose SA | AC below | | | |
| | SAC | Single Function | Through Drive | e Control | I with R-net 9 | 90-amp or 12 | 20-amp controller | | N/C |
| | | | activation of si | • . | • | | | | |
| | | • | • | | • | | sticks, Omni 2 and spe | • | |
| | | | | - | | - | tible with memory seat | _ | |
| • | | | • | BELOW A | ARE COMPAT | IBLE ONLY V | WHEN CHOOSING SAC | C ABOVE) | |
| | SACMEMORY | Memory Seat P | • | | | | | | \$1,495 |
| _ | 05/ 507/04/ 05/ | - | | | - | | (ECELJ and ECELJL) | | |
| • | | | | з то Рои | VER OPTIONS | THROUGH L | DRIVE CONTROLS AND | THROUGH EXTERNAL S | |
| | | Single Toggle S | | | | Attendant Activation | \$410 | | |
| | SACPUSH1 | Single Push Bu | | _ | • | | User Activation | Attendant Activation | \$400 |
| | SACPUSH2 | Dual Push Butte | on Switch – (D | ual Mode | e: SAC) | | User Activation | Attendant Activation | \$490 |
| | SACSSBS | Buddy Button Switch | Black | Red | Green | Yellow | User Activation | Attendant Activation | \$540 |
| | SACSSES | Egg Switch-Bla | ck | | | | User Activation | Attendant Activation | \$426 |
| | SACSSML | Ultra Light Swit | ch | | | | User Activation | Attendant Activation | \$605 |







| DUAL SEAT FUNCTIONS THROUGH DRIVE CONTROL EPSV2 Dual Function Through Drive Control with VR2 Non-Expandable Electronics Allows for the activation of 2 power options through the VR2 Controller. Combination of TILT + RECLINE or ELEVATE + RECLINE are not possible with EPSV2 A Does not allow for control of power options through drive control and separate switches VR2 Electronics can only accommodate specific power seat combinations such as Tilt + Power Center Mount / Tilt + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs MAC E-BX Multiple Function through Drive Control with Expandable Electronics — Powers iQ Actuators Required with the combined selection of the 90° Power Center Mount Elevating & Articulating Foot Platform (ADDPF) and the narrow base configuration (FS2221B) MAC ACPTIONS MACMEMORY Memory Seat Program S175 SELECTION OF SWITCH BELOW GIVES ACCESS TO POWER OPTIONS THROUGH DRIVE CONTROLS AND THROUGH EXTERNAL SWITCH MACKEYPAD-T Keypad w/ 5 Toggle Switches User Activation Attendant Activation 3445 MACMULTI 4-Way Toggle Switch — (Up to 4 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this swit | 35. | ELECTRON | ICS | - MULT | IPLE | SEAT | FUNC | CTION CC | NTRO | L TYPI | E | | | | | |
|--|-------------|------------------|--|-----------|--|-----------|---------|-------------|------------|------------|-----------|---------------|----------------|------------|---------|------------|
| A Allows for the activation of 2 power options through the VR2 Controller. Combination of TILT + RECLINE or ELEVATE + RECLINE are not possible with EPSV2 A Does not allow for control of power options through drive control and separate switches VR2 Electronics can only accommodate specific power seat combinations such as TIIH + Power Center Mount / Tilt + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs / Required with the combined selection of the 90° Power Center Mount Elevating & Articulation Foot Platform (ADDPF) and the narrow base configuration (F322218) MACCHONNS MACMEMORY Memory Seat Program \$175 ***MACMEMORY Memory Seat Program \$175 ***SELECTION OF SWITCH BELOW GIVES ACCESS TO POWER OPTIONS THROUGH DRIVE CONTROLS AND THROUGH EXTERNAL SWITCH MACKEYPAD-P Keypad w/ 5 Toggle Switches User Activation Attendant Activation \$445 ***MACKEYPAD-P Keypad w/ 5 Toggle Switches User Activation Attendant Activation \$445 ***MACKEYPAD-P Keypad w/ 5 Toggle Switch - (Up to 4 Activations) User Activation Attendant Activation \$180 ***A By selecting this switch, memory recall is only available through the Joystick. ***MACPUSH4 | • | DUAL SEAT FU | INCT | IONS TH | ROUGH | I DRIVE | CONT | ROL | | | | | | | | |
| LEVAITE + RECLINE are not possible with EPSV2 A Does not allow for control of power options through drive control and separate switches VR2 Electronics can only accommodate specific power seat combinations such as Till + Power Center Mount / Till + Combined Power Legs / Recline + Power Center Mount / Recline + Combined Power Legs MULTIPLE SEAT FUNCTIONS THROUGH R-WET MAC E-BX Multiple Function through Drive Control with Expandable Electronics — Powers iQ Actuators \$2,295 Required with the combined selection of the 90° Power Center Mount Elevating & Articulating Foot Platform (ADDPF) and the narrow base configuration (FS22218) MAC OPTIONS MACMEMORY MEMORY Seat Program \$175 SELECTION OF SWITCH BELOW GIVES ACCESS TO POWER OPTIONS THROUGH DRIVE CONTROLS AND THROUGH EXTERNAL SWITCH MACKEYPAD-P MACKEYPAD-P MACKEYPAD-P MACKEYPAD-P MACKEYPAD-T MACWAIT 4-Way Toggle Switches User Activation Attendant Activation \$445 MACMULTI 4-Way Toggle Switch — (Up to 4 Activations) User Activation Attendant Activation \$180 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch User Activation Attendant Activation \$225 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch Told Push Push Push Push Push Push Push Push | | EPSV2 | Dua | ıl Functi | on Thro | ough Dr | rive Co | ontrol with | √R2 Noi | n-Expar | ndable E | lectronics | | | | N/C |
| A Does not allow for control of power options through drive control and separate switches A VR2 Electronics can only accommodate specific power seat combinations such as Tilt + Power Center Mount / Tilt + Combined Power Legs MULTIPLE SEAT FUNCTIONS THROUGH R-NET MAC E-BX Multiple Function through Drive Control with Expandable Electronics — Powers iQ Actuators \$2,295 A Required with the combined selection of the 90° Power Center Mount Elevating & Articulating Foot Platform (ADDPF) and the narrow base configuration (FS2221B) MAC OPTIONS MACMEMORY MACMULTI 4-Way Toggle Switch — (Up to 4 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACMULTI Triple Toggle Switch — (Up to 5 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch of the Striple St | | | | Allows | for the | activati | on of 2 | power opt | ions thro | ough the | | | mbination of T | TILT + REC | CLINE o | r |
| NULTIPLE SEAT FUNCTIONS THROUGH R-NET | | | A | | | | | • | | | ve contro | ol and separ | ate switches | | | |
| ### ACC #### ACC ###################### | | | A | VR2 Ele | ectronic | s can o | nly acc | commodate | specific | power | seat con | nbinations s | uch as Tilt + | | nter Mo | unt / Tilt |
| Required with the combined selection of the 90° Power Center Mount Elevating & Articulating Foot Platform (ADDPF) and the narrow base configuration (FS2221B) MACC OPTIONS MACMEMORY Memory Seat Program \$175 | > | MULTIPLE SEA | T FU | NCTION | TIONS THROUGH R-NET | | | | | | | | | | | |
| MAC OPTIONS MACMEMORY MACKEYPAD-P Keypad w/ 5 Push Button Switch MACKEYPAD-T Triple Toggle Switch- (Up to 5 Activations) MACPUSH4 MACPUSH4 MACPUSH5 MACPUSH5 MACPUSH5 MACRUCH ACTIVATION HAND MOUNT Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) Mount Tallored SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ST\$14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C ST\$17-22-21 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C ST\$17-22-22 Width adjustment from 14" to 122" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C ST\$17-22-22 Width adjustment from 14" to 122" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C ST\$17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 19" (SOSW15) | | MAC | E-B | X Multip | fultiple Function through Drive Control with Expandable Electronics – Powers iQ Actuators \$ | | | | | | \$2,295 | | | | | |
| MACMEMORY Memory Seat Program SELECTION OF SWITCH BELOW GIVES ACCESS TO POWER OPTIONS THROUGH DRIVE CONTROLS AND THROUGH EXTERNAL SWITCH MACKEYPAD-P Keypad w/ 5 Push Button Switches User Activation Attendant Activation \$445 MACKEYPAD-T Keypad w/ 5 Toggle Switches User Activation Attendant Activation \$445 MACMULTI Triple Toggle Switch (Up to 4 Activations) User Activation Attendant Activation \$180 ■ By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 **Way Push Button Switch **By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 **By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 **By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 **By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 **By selecting this switch, memory recall is only available through the Joystick. **By selecting this switch, memory recall is only available through the Joystick. **By selecting this switch, memory recall is only available through the Joystick. **SELECTION ATTERIOR TO ACTIVATION HAND MOUNT **SWITCH ACTIVATION HAND MOUNT **SWITCH ACTIVATION HAND MOUNT SWITCH Install Switch on LH side) TSML - (Install Switch on RH side) TSMR - (Install Switch on RH side) N/C **Deack angles of 102° or greater are not compatible with the OMNI 2. **Back angles of 102° or greater are not compatible with the OMNI 2. **SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C **The minimum seat depth available with this option is 18" (455 MM) The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 18" (SOSW15) 18" (SOSW16) 17" (SOSW17) 18" (SOSW18) | | | A | | | | | | | | Center M | lount Elevat | ing & Articula | ting Foot | Platfor | m |
| ► SELECTION OF SWITCH BELOW GIVES ACCESS TO POWER OPTIONS THROUGH DRIVE CONTROLS AND THROUGH EXTERNAL SWITCH MACKEYPAD-P Keypad w/ 5 Push Button Switches User Activation Attendant Activation \$445 MACKEYPAD-T Keypad w/ 5 Toggle Switches User Activation Attendant Activation \$445 MACMULTI 4-Way Toggle Switch – (Up to 4 Activations) User Activation Attendant Activation \$180 MACMULTIT Triple Toggle Switch – (Up to 5 Activations) User Activation Attendant Activation \$135 MACPUSH4 4-Way Push Button Switch User Activation Attendant Activation \$225 MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 Macy Selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 Macy Selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 Macy Selecting this switch, memory recall is only available through the Joystick. Macy Selecting this switch, memory recall is only available through the Joystick. | • | MAC OPTIONS | | | | | | | | | | | | | | |
| MACKEYPAD-P Keypad w/ 5 Push Button Switches MACKEYPAD-T Keypad w/ 5 Toggle Switches User Activation Attendant Activation \$445 MACMULTI 4-Way Toggle Switch - (Up to 4 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACMULTIT Triple Toggle Switch - (Up to 5 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW15) 19" (SOSW17) | | MACMEMORY | Mer | nory Se | at Prog | ıram | | | | | | | | | | \$175 |
| MACKEYPAD-T Keypad w/ 5 Toggle Switches MACMULTI 4-Way Toggle Switch – (Up to 4 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACMULTIT Triple Toggle Switch – (Up to 5 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML – (Install Switch on LH side) TSMR – (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C MACPUSH A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 16" to 19" (380 - 480 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | > | SELECTION OF | SWI | TCH BEL | .OW G/\ | /ES AC | CESS T | O POWER | OPTIONS | THROU | JGH DRI\ | E CONTRO | LS AND THRO | UGH EXT | ERNAL | SWITCH |
| MACMULTI 4-Way Toggle Switch – (Up to 4 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACMULTIT Triple Toggle Switch – (Up to 5 Activations) A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML – (Install Switch on LH side) TSMR – (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | MACKEYPAD-P | Key | pad w/ s | 5 Push | Button | Switch | nes | | | User | Activation | Atten | dant Activ | ation | \$445 |
| MACMULTIT Triple Toggle Switch - (Up to 5 Activations) MACPUSH4 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 A-Way Push Button Switch MACPUSH5 S-Way Push Button Switch MACPUSH5 By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch MACPUSH5 S-Way Push Button Switch By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 S-Way Push Button Switch By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | MACKEYPAD-T | Key | pad w/ s | 5 Toggl | e Switc | hes | | | | User | Activation | Atten | dant Activ | ation | \$445 |
| MACMULTIT Triple Toggle Switch – (Up to 5 Activations) User Activation Attendant Activation \$135 ▲ By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch User Activation Attendant Activation \$225 ▲ By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 ▲ By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML – (Install Switch on LH side) TSMR – (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) N/C STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) </th <th></th> <th>MACMULTI</th> <th>4-W</th> <th>ay Togg</th> <th>jle Swit</th> <th>ch – (U</th> <th>lp to 4</th> <th>Activations</th> <th>s)</th> <th></th> <th>User</th> <th>Activation</th> <th>Atten</th> <th>dant Activ</th> <th>ation</th> <th>\$180</th> | | MACMULTI | 4-W | ay Togg | jle Swit | ch – (U | lp to 4 | Activations | s) | | User | Activation | Atten | dant Activ | ation | \$180 |
| A By selecting this switch, memory recall is only available through the Joystick. MACPUSH4 4-Way Push Button Switch User Activation Attendant Activation \$225 A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch User Activation Attendant Activation \$240 A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML − (Install Switch on LH side) TSMR − (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ■ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) ST\$14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C ST\$14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) ST\$17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ST\$17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | A | By sele | cting th | nis swite | ch, mei | mory recall | is only a | available | e through | the Joystic | ck. | | | |
| MACPUSH4 4-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML − (Install Switch on LH side) TSMR − (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | MACMULTIT | Triple Toggle Switch – (Up to 5 Activations) | | | | | | User | Activation | Atten | dant Activ | ation | \$135 | | |
| A By selecting this switch, memory recall is only available through the Joystick. MACPUSHS 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML − (Install Switch on LH side) TSMR − (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | A | By sele | cting th | nis swite | ch, mei | mory recall | is only a | available | e through | the Joystic | ck. | | | |
| MACPUSH5 5-Way Push Button Switch A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) TSMR - (Install Switch on RH side) TSMR - (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | MACPUSH4 | 4-W | ay Push | ay Push Button Switch User Activation Attendant Activation | | | | | | | \$225 | | | | |
| A By selecting this switch, memory recall is only available through the Joystick. 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | A | By sele | cting th | nis swite | ch, mei | mory recall | is only a | available | e through | the Joystic | ek. | | | |
| 36. SWITCH ACTIVATION HAND MOUNT Switch Installation: TSML − (Install Switch on LH side) TSMR − (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | MACPUSH5 | 5-W | ay Push | n Buttor | n Switcl | h | | | | User | Activation | Atten | dant Activ | ation | \$240 |
| Switch Installation: TSML - (Install Switch on LH side) TSMR - (Install Switch on RH side) N/C 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) \$86° 90° 94° 98° 102° 106° 110° N/C Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) N/C STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | A | By sele | cting th | nis swite | ch, mei | mory recall | is only a | available | e through | the Joystic | ck. | | | |
| 37. SIGNATURE TAILORED SOLUTIONS - PRE-SET BACK ANGLE (FOR NON-RECLINING BACKS) SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C \$TS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C \$The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | 36. | SWITCH AC | TIV | NOITA | HAND | MOUI | NT | | | | | | | | | |
| SOBAA Select one: 86° 90° 94° 98° 102° 106° 110° N/C ▶ Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | Sw | itch Installatio | n: | | | TSML - | – (Inst | all Switch | on LH | side) | | TSMR - (I | nstall Switc | h on RH | side) | N/C |
| Back angles of 102° or greater are not compatible with the OMNI 2. 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C A The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | 37. | SIGNATURE | E TA | ILORE | D SOL | .UTIOI | NS - P | RE-SET | BACK | ANGLE | E (FOR | NON-REC | LINING BA | ACKS) | | |
| 38. SIGNATURE TAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 14" AND 22" (355 - 560 MM) STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C **The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C **The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | SOBAA | Sel | ect one: | | 86° | | 90° | 94 | 0 | 98° | 102 | 2° 10 | 6° | 110° | N/C |
| STS14-19-19 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | | | > | Back | angles | of 102° or | greater a | are not d | compatib | le with the (| OMNI 2. | | | |
| STS14-19-22 Width adjustment from 14" to 19" (355-480 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | 38. | SIGNATURE | TAI | LORE | SOL | JTION | S-AD | JUSTAB | LE SEA | T WID | TH RAN | IGE BETV | VEEN 14" A | ND 22" (| 355 - 5 | 60 MM) |
| ▲ The minimum seat depth available with this option is 18" (455 MM) STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | STS14-19-19 | V | Vidth ad | justmer | nt from | 14" to | 19" (355-4 | 80 MM) | and De | epth rang | ge of 15" to | 19" (380 - 48 | 80 MM) | | N/C |
| STS17-22-19 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 15" to 19" (380 - 480 MM) N/C STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | STS14-19-22 | ٧ | Vidth ad | justmer | nt from | 14" to | 19" (355-4 | 80 MM) | and De | epth rang | ge of 18" to | 22" (455 - 56 | 80 MM) | | N/C |
| STS17-22-22 Width adjustment from 17" to 22" (430-560 MM) and Depth range of 18" to 22" (455 - 560 MM) N/C ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | | _ | The | minimu | m seat | depth a | available w | ith this c | ption is | 18" (455 | 5 MM) | | | | |
| ▲ The minimum seat depth available with this option is 18" (455 MM) 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | STS17-22-19 | V | Vidth ad | justmer | nt from | 17" to | 22" (430-5 | 60 MM) | and De | epth rang | ge of 15" to | 19" (380 - 48 | 80 MM) | | N/C |
| 14" (SOSW14) 15" (SOSW15) 16" (SOSW16) 17" (SOSW17) 18" (SOSW18) 19" (SOSW19) | | STS17-22-22 | V | Vidth ad | justmer | nt from | 17" to | 22" (430-5 | 60 MM) | and De | epth rang | ge of 18" to | 22" (455 - 56 | 60 MM) | | N/C |
| | | | | ▲ The | minimu | m seat | depth a | available w | ith this o | ption is | 18" (455 | і ММ) | - | | | |
| 20" (COCM20) 24" (COCM24) 22" (COCM22) | | 14" (SOSW14 |) | 15" (| SOSW | 15) | 16" | (SOSW16 |) 1 | 17" (SO | SW17) | 18 | " (SOSW18) | 19 |)" (SOS | SW19) |
| 20" (SOSW20) 21" (SOSW21) 22" (SOSW22) | | 20" (SOSW20 |) | 21" (| SOSW | 21) | 22" | (SOSW22 | | | | | | | | |







| 39. | SIGNATURE T | FAILORED SOLUTIONS - ADJUSTABLE SEAT WIDTH RANGE BETWEEN 20" AND 24" (510 - 6 | 310 MM) | | | | | | | | |
|----------|-------------------|---|--------------|--|--|--|--|--|--|--|--|
| | STS20-25-22 | Width adjustment from 20" to 25" (510-635 MM) and Depth range of 18" to 22" (455 - 560 MM) | N/C | | | | | | | | |
| | | ▲ Seat width of 25" is a custom dimension and require an (RFQ) | | | | | | | | | |
| | | ▲ 23" and 24" Seat widths are not compatible with the N2221 - Narrow 21" base width option (FS2221B) | | | | | | | | | |
| | | ▲ The minimum seat depth available with this option is 18" (455 MM) | | | | | | | | | |
| | 20" (SOSW20) | 21" (SOSW21) 22" (SOSW22) 23" (SOSW23) 24" (SOSW24) | | | | | | | | | |
| 40. | SIGNATURE T | TAILORED SOLUTIONS - ADJUSTABLE SEAT DEPTH RANGE BETWEEN 15" AND 22" (380 - 56 | 60 MM) | | | | | | | | |
| | 15" (SODN15) | 16" (SODN16) 17" (SODN17) 18" (SODN18) 19" (SODN19) 20" (SODN20) | N/C | | | | | | | | |
| | 21" (SODN21) | 22" (SODN22) 18" is the minimum possible seat depth when choosing a 22" long Seat Pan (STS14-19-22, STS14-22-22 and STS20-25-22) | N/C | | | | | | | | |
| | | TAILORED SOLUTIONS - EXTRUDED BACK CANE HEIGHT (THE MEASUREMENT IS TAK PAN TO THE TOP OF THE BACK CANE) | EN | | | | | | | | |
| • | Not compatible w | with a power or manual recline | | | | | | | | | |
| | 16" (SOBCH16) | 17" (SOBCH17) 18" (SOBCH18) 19" (SOBCH19) | | | | | | | | | |
| ▼ | 20" is the minimu | num back height required with a power or manual recline | | | | | | | | | |
| | 20" (SOBCH20) | 21" (SOBCH21) 22" (SOBCH22) 23" (SOBCH23) 24" (SOBCH24) 25" (SO | BCH25) | | | | | | | | |
| | 26" (SOBCH26) | 27" (SOBCH27) 28" (SOBCH28) | | | | | | | | | |
| 41. | 5 SIGNATURE | TAILORED SOLUTIONS - BACK CANE OPTIONS | | | | | | | | | |
| • | PUSH HANDLES | | | | | | | | | | |
| | SOPH | Push Handles (pair) | N/C | | | | | | | | |
| • | | ACK CANES FOR NON-RECLINING BACKS | | | | | | | | | |
| | STSENDO-F1 | Endomorph Back Canes for non-reclining backs, 1 IN (25 MM) total | \$120 | | | | | | | | |
| | STSENDO-F2 | Endomorph Back Canes for non-reclining backs, 2 IN (50 MM) total | \$120 | | | | | | | | |
| | STSENDO-F3 | Endomorph Back Canes for non-reclining backs, 3 IN (75 MM) total | \$120 | | | | | | | | |
| | STSENDO-F4 | Endomorph Back Canes for non-reclining backs, 4 IN (100 MM) total | \$120 | | | | | | | | |
| • | | ACK CANES FOR RECLINING BACKS | | | | | | | | | |
| | STSENDO-R1 | Endomorph Back Canes for reclining backs, 1 IN (25 MM) total | N/C | | | | | | | | |
| _ | STSENDO-R2 | Endomorph Back Canes for reclining backs, 2 IN (50 MM) total | N/C | | | | | | | | |
| V | | REST (FOR NON-RECLINING BACKS) | #0.40 | | | | | | | | |
| | STSFB | Folding Backrest for Storage/Travel Access for non-reclining backs | \$240 | | | | | | | | |
| 42. | BACK SUPPO | ORT | | | | | | | | | |
| | DSTR-WWHH | Adjustable Tension Back Upholstery, WW x HH | | | | | | | | | |
| | | Only available with Dual Post armrests (SOADP) | | | | | | | | | |
| | STDSB-WWHH | Contour back support up to 21" wide, with a maximum shell height of 22". | | | | | | | | | |
| | | ▲ The minimum space between the back and seat pan is 4" (± 1") with a fixed back and 6" (± 1") with a reclining back | | | | | | | | | |
| | STDSB-WWHH | | \$755 | | | | | | | | |
| | | ▲ The minimum space between the back and seat pan is 4" (± 1") with a fixed back and 6" (± 1") with a reclin | | | | | | | | | |
| | STDSB-WWHH | | \$1,075 | | | | | | | | |
| | | ▲ The minimum space between the back and seat pan is 4" (± 1") with a fixed back and 6" (± 1") with a reclin | ing back | | | | | | | | |







| 42. | BACK SUPPO | RT (CONTINUED) | | | | |
|-----|----------------------|--|----------|--|--|--|
| | | (| | | | |
| • | MATRX BACKS E2S-WWHH | MATRX ELITE E2S BACK – (14" to 20" Wide - Back height of 6" to 20", in 2" increments) | \$99 | | | |
| | E23-VVVIII | Back shell height is available in 6" to 20", in 2" increments. The minimum space between the back and | • | | | |
| | | pan is 4" (± 1") with a fixed back and 6" (± 1") with a reclining back | Jeur | | | |
| | | ▲ Weight capacity up to 300 lb | | | | |
| | E2D-WWHH | MATRX DEEP CONTOUR ELITE E2D BACK – (14" to 20" Wide - Back height of 6" to 20", in 2" increments) | \$1,15 | | | |
| | | Back shell height is available in 6" to 20", in 2" increments. The minimum space between the back and pan is 4" (\pm 1") with a fixed back and 6" (\pm 1") with a reclining back | seat | | | |
| | | ▲ This product is not compatible with Lateral Trunk Supports | | | | |
| | | ▲ Weight capacity up to 300 lb | | | | |
| | PBE-WWHH-TR | MATRX ELITE TR BACK – (15" to 20" Wide - Back height of 14", 16", 18" and 20") | \$91 | | | |
| | | Back shell height is available in 14", 16" 18" or 20". The minimum space between the back and seat part 1") with a fixed back and 6" (± 1") with a reclining back | is 4" (: | | | |
| | | ▲ Weight capacity up to 300 lb | | | | |
| | PBE-WWHH-HD | MATRX HEAVY DUTY ELITE BACK - (21" to 24" Wide - Back height of 16" and 20") | \$1,15 | | | |
| | | Back shell height is available in 16" or 20". The minimum space between the back and seat pan is 4" (± a fixed back and 6" (± 1") with a reclining back | 1") wit | | | |
| | | ▲ Weight capacity up to 500 lb | | | | |
| | EDB-WWHH-HD | MATRX ELITE DEEP HD BACK - (21" to 24" Wide - Back height of 16", 18" and 20") | \$1,19 | | | |
| | | Back shell height is available in 16", 18" or 20". The minimum space between the back and seat pan is with a fixed back and 6" (± 1") with a reclining back | 4" (± 1' | | | |
| | | ▲ This product is not compatible with Lateral Trunk Supports | | | | |
| | | ▲ Weight capacity up to 500 lb | | | | |
| • | NXT BACKS | | | | | |
| | NOACB-WWHH | NXT OPTIMA FH AC CONTOUR BACK – (15" to 21" Wide) | \$69 | | | |
| | | ▲ Weight capacity up to 300 lb | | | | |
| | NOACB-WWHH | NXT OPTIMA FH AC CONTOUR BACK – (22" to 28" Wide) | \$72 | | | |
| | | ▲ Weight capacity up to 550 lb | | | | |
| | | Back shell heights only come in 13", 16" or 19" high. The minimum space between the back and seat pa (± 1") with a fixed back and 6" (± 1") with a reclining back | nn is 4" | | | |
| | NOPCB-WWHH | NXT OPTIMA FH PC DEEP CONTOUR BACK – (15" to 21" Wide) | \$79 | | | |
| | | ▲ Weight capacity up to 300 lb | | | | |
| | NOPCB-WWHH | NXT OPTIMA FH PC DEEP CONTOUR BACK – (22" to 28" Wide) | \$82 | | | |
| | | ▲ Weight capacity up to 550 lb | | | | |
| | | ▲ This product is not compatible with Lateral Trunk Supports | | | | |
| | | Back shell heights only come in 13", 16" or 19" high. The minimum space between the back and seat pa (± 1") with a fixed back and 6" (± 1") with a reclining back | \$820 | | | |
| • | OMISSION OF TH | E BACK SUPPORT | | | | |
| | STDSBO | Omission of the Contour Back Support ◀ Specify: | N/ | | | |
| | STDSBO- UNIVBKT | Universal 4-Point Fixed Brackets for Aftermarket Backs | \$18 | | | |
| 3. | BACK SUPPO | RT TOTAL HEIGHT (MEASURED FROM THE SEAT PAN TO THE TOP OF THE BACK) | | | | |
| | | ▼ 20" is the minimum back height required with a reclining back. | | | | |
| | 16" (SOBH16) | 18" (SOBH18) 20" (SOBH20) 22" (SOBH22) 24" (SOBH24) 26" (SOBH26) 28" (SOBH26) | SOBH28 | | | |







| 44. | SEAT CUSHIONS | | | | | | | | | |
|-------------|---|---|-------|--|--|--|--|--|--|--|
| • | PERFORMA CG AIR | - THERAPEUTIC AIR CUSHION | | | | | | | | |
| | Custom Cushion (I | Please use the Performa CG Air order form) | | | | | | | | |
| Ce | II Height (Choose 1) | · | | | | | | | | |
| > | SINGLE (1) VALVE - DESIRED COVER TYPE, DIMENSIONS AND PRICING | | | | | | | | | |
| | ► PERFORMA CG AIR CUSHION WITH STANDARD SPACER KNIT COVER | | | | | | | | | |
| | CGA1VSCxxxx-x | 14" to 20" (355 mm to 510 mm) wide | \$696 | | | | | | | |
| | CGA1VSCxxxx-x | 22" + (560 mm +) wide | \$783 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| | ► PERFORMA CG A | IR CUSHION WITH 3D SPACER KNIT DOUBLE LAYER COVER | | | | | | | | |
| | CGA1V3Dxxxx-x | 14" to 20" (355 mm to 510 mm) wide | \$735 | | | | | | | |
| | CGA1V3Dxxxx-x | 22" + (560 mm +) wide | \$825 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| | ► PERFORMA CG A | IR CUSHION WITH EXTERNAL INCONTINENCE COVER | | | | | | | | |
| | CGA1VICxxxx-x | 14" to 20" (355 mm to 510 mm) wide | \$785 | | | | | | | |
| | CGA1VICxxxx-x | 22" + (560 mm +) wide | \$830 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| • | DUAL (2) VALVE - DI | ESIRED COVER TYPE, DIMENSIONS AND PRICING | | | | | | | | |
| | ► PERFORMA CG A | IR CUSHION WITH STANDARD SPACER KNIT COVER | | | | | | | | |
| | CGA2VSCxxxx-x | 14" to 20" (355 mm to 510 mm) wide | \$696 | | | | | | | |
| | CGA2VSCxxxx-x | 22" + (560 mm +) wide | \$783 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| | ► PERFORMA CG A | IR CUSHION WITH 3D SPACER KNIT DOUBLE LAYER COVER | | | | | | | | |
| | CGA2V3Dxxxx-x | 14" to 20" (355 mm to 510 mm) wide | \$735 | | | | | | | |
| | CGA2V3Dxxxx-x | 22" + (560 mm +) wide | \$825 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| | | IR CUSHION WITH EXTERNAL INCONTINENCE COVER | | | | | | | | |
| | | 14" to 20" (355 mm to 510 mm) wide | \$785 | | | | | | | |
| | CGA2VICxxxx-x | 22" + (560 mm +) wide | \$830 | | | | | | | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | | | | | | | | |
| | | SHION SEGMENTATION (PLEASE SELECT 1 BOX) | | | | | | | | |
| | | CG Air Dual Valves with Left / Right Location | N/C | | | | | | | |
| | CGA-2VF6 | CG Air Dual Valves with Front / Back Location, Front distance 6 in (150 mm) from the front | N/C | | | | | | | |
| | CGA-2VF8 | CG Air Dual Valves with Front / Back Location, Front distance 8 in (205 mm) from the front | N/C | | | | | | | |
| | CGA-2VF10 | CG Air Dual Valves with Front / Back Location, Front distance 10 in (255 mm) from the front | N/C | | | | | | | |
| | PERFORMA CG AIR | | | | | | | | | |
| | CGA-GZ | GripZone Anti-Slip Technology | \$75 | | | | | | | |
| | CGA-TT-WW | Transfer Trellis | \$125 | | | | | | | |
| | CGA-AC | Anatomic Contour Seat Insert | \$140 | | | | | | | |
| | CGA-SP | Seat Pouch | \$44 | | | | | | | |
| • | CONTOUR SEAT CUS | | | | | | | | | |
| | SCPSC-WWDD | Contour Seat Cushion up to 19" Wide | \$620 | | | | | | | |
| | SCPSC-WWDD | Contour Seat Cushion for Non-Standard Sizes of 20" to 24" Wide | \$735 | | | | | | | |







| • | MATRX CUSHION | | |
|-------------|---------------------|--|----------|
| | PSP-WWHH | MATRX PSP Seat Cushion – (11" to 20" Wide) | \$64 |
| | | ▲ The maximum user weight capacity is 300 lb | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | |
| | PSP-WWHH | MATRX PSP Seat Cushion – (22" to 26" Wide) | \$998 |
| | | ▲ The maximum user weight capacity is 550 lb | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | |
| > | NXT BIO-FIT CUS | | |
| | NXTBIOFIT-WWI | NXT BIO FIT Cushion – (15" to 21" Wide) | \$59 |
| | | ▲ The maximum user weight capacity is 300 lb | |
| | NXTBIOFIT-WWI | , , | \$62 |
| | | ▲ The maximum user weight capacity is 400 lb | |
| | | ▲ Cushion sizes only come in even numbers for width and depth measurements. | |
| | | AILORED SOLUTIONS - CANTILEVER ARMRESTS - ADJUSTABLE HEIGHT, INWARD/ | |
| | | ION AND VERTICAL ANGLE. ALLOWS ARMPAD TO MOVE 1" FORWARD (CHOOSE 2 |) |
| | R NON-RECLINING | | |
| ▼ | | from 7.25" (185 mm) to 15.25" (385 mm) in 1" (25 mm) increments th Waterfall Armpads (SOWAPx et SOWGELx) | |
| • | | Signature Cantilever Armrest – Desk Length 12" (305 mm) - Left Side | N/C |
| | | Signature Cantilever Armrest – Desk Length 12" (305 mm) - Right Side | N/C |
| | | | |
| | | Signature Cantilever Armrest – Full Length 16" (405 mm) - Left Side | N/0 |
| | | Signature Cantilever Armrest – Full Length 16" (405 mm) - Right Side | N/C |
| | SOAFBELH | Signature Cantilever Armrest – Extended Length 18" (455 mm) - Left Side | N/C |
| | SOAFBERH | Signature Cantilever Armrest – Extended Length 18" (455 mm) - Right Side | N/C |
| A | _ | th 18" (455 mm) armrests are only compatible with the extra-long armpads (16" x 3 $^{1}\!\!\!/_2$ ") (SOXWFAP16 or SO | XWGAP16) |
| ▼ | CUSTOM LENGT | | |
| | | Signature Cantilever Armrest – Custom Length 20" (510 mm) - Left Side | \$98 |
| | | Signature Cantilever Armrest – Custom Length 20" (510 mm) - Right Side | \$98 |
| | | Signature Cantilever Armrest – Custom Length 22" (560 mm) - Left Side | \$98 |
| | SOAFBCRH | Signature Cantilever Armrest – Custom Length 22" (560 mm) - Right Side | \$95 |
| | The custom-length 2 | 0" (510 mm) and 22" (560 mm) armrests are only compatible with the extra-long armpads (16" x 3 $^{1}\!\!/_{2}$ ") (SOXWFAP16 or SC | XWGAP16) |
| FOI | R RECLINING BAC | | |
| ▼ | | from 10.25" (260 mm) to 16.25" (415 mm) in 1" (25 mm) increments | |
| • | Choose a Height I | , | 5 mm) |
| ▼ | - | th Waterfall Armpads (SOWAPx and SOWGELx) | |
| | | Signature Cantilever Armrest for Reclining Back – Desk Length 12" (305 mm) - Left Side | N/C |
| | | Signature Cantilever Armrest for Reclining Back – Desk Length 12" (305 mm) - Right Side | N/C |
| | | Signature Cantilever Armrest for Reclining Back – Full Length 16" (405 mm) - Left Side | N/C |
| | | Signature Cantilever Armrest for Reclining Back – Full Length 16" (405 mm) - Right Side | N/C |
| | SOAFBELH-R | Signature Cantilever Armrest for Reclining Back – Extended Length 18" (455 mm) - Left Side | N/C |
| | SOAFBERH-R | Signature Cantilever Armrest for Reclining Back – Extended Length 18" (455 mm) - Right Side | N/C |
| A | | th 18" (455 mm) armrests are only compatible with the extra-long armpads (16" x 3 $^{\prime}\!\!\!/_2$ ") (SOXWFAP16 or SO | XWGAP16) |
| ▼ | CUSTOM LENGT | | |
| | | Signature Cantilever Armrest for Reclining Back – Custom Length 20" (510 mm) - Left Side | \$98 |
| | SOAFBCRH-R | Signature Cantilever Armrest for Reclining Back – Custom Length 20" (510 mm) - Right Side | \$9 |
| | SOAFBCLH-R | Signature Cantilever Armrest for Reclining Back – Custom Length 22" (560 mm) - Left Side | \$98 |
| | | | \$98 |

Left Hand

Dight Hand







46. DUAL POST - HEIGHT ADJUSTABLE ARMRESTS - INCLUDES TRANSFER GRIPS (FOR NON-RECLINING **BACKS - CHOOSE 2)**

▼ NOT compatible with the extra-long armpads (16" x 3 ½") (SOXWFAP16 or SOXWGAP16) and the Arm Trough with Hand Support (SOCAR)

| SOADPDLH | Dual Post Height Adjustable – Desk Length Left Side – (Height Adjustable from 10 $\frac{1}{4}$ " to 15 $\frac{1}{4}$ " with $\frac{1}{2}$ " increments) | \$168 |
|----------|--|-------|
| SOADPDRH | Dual Post Height Adjustable – Desk Length Right Side – (Height Adjustable from 10 $\frac{1}{4}$ " to 15 $\frac{1}{4}$ " with $\frac{1}{2}$ " increments) | \$168 |
| SOADPFLH | Dual Post Height Adjustable – Full Length Left Side – (Height Adjustable from 10 $\frac{1}{4}$ " to 15 $\frac{1}{4}$ " with $\frac{1}{2}$ " increments) | \$168 |
| SOADPFRH | Dual Post Height Adjustable – Full Length Right Side – (Height Adjustable from 10 ¼" to 15 ¼" with ½" increments) | \$168 |

48. ARMREST HEIGHT ADJUSTMENT AT FACTORY

- Set the Armrest Height at:
 - ▲ The Armrest Height is taken from the seat pan to the top of the armpad.
 - ▲ Not required for Dual Post.

49. SIGNATURE TAILORED SOLUTIONS - ARMPADS

| FOAM TYPE SELECT | ION |
|------------------|-----|
|------------------|-----|

| SOFAPD | Desk Length Flat Armpad – (10 ½" x 2 ½") | Select side: | Left Hand Side | Right Hand Side | STD |
|-----------|--|--------------|-------------------|--------------------|-----|
| SOFAPF | Full Length Flat Armpad – (14" x 2 ½") | Select side: | Left Hand Side | Right Hand Side | STD |
| SOXWFAP10 | X-Wide 3.5" (90 mm) Flat FOAM Armpad, 10" (255 mm) Long | Select side: | Left Hand Side | Right Hand Side | N/C |
| SOXWFAP14 | X-Wide 3.5" (90 mm) Flat FOAM Armpad, 14" (355 mm) Long | Select side: | Left Hand Side | Right Hand Side | N/C |
| SOXWFAP16 | X-Wide 3.5" (90 mm) Flat FOAM Armpad, 16" (405 mm) Long | Select side: | Left Hand Side | Right Hand Side | N/C |

- The X-Wide 16" x 3 1/2" Armpads require Cantilever (SOAFBExx) armrests with an extended length of 18" (455 mm) or more
- The X-Wide 16" x 3 1/2" Armpads are NOT compatible with Dual Post Armrests (SOADPxx)

| SOWAPD | De | sk Length Waterfall – (8 ½" x 2 ¾") | side: | Side | Side | N/C |
|--------|----------|---|----------------|------------------------|--------------------|-----|
| | A | May interfere with flipping back the armrests w | hen combined w | vith Lateral Trunk sup | ports. | |
| | A | NOT compatible with Cantilever (SOAFBxxx) | | | | |
| SOWAPF | Ful | I Length Waterfall – (13" x 2 ¾") | Select side: | Left Hand Side | Right Hand Side | N/C |
| | A | May interfere with flipping back the armrests w | hen combined w | vith Lateral Trunk sup | ports. | |
| | A | NOT compatible with Cantilever (SOAFBxxx) | | | | |

HYBRID GEL AND FOAM TYPE SELECTION (THE GEL ALWAYS STAYS SOFT)

| SOGELD | Desk Length Hybrid Gel and Foam Flat armpad – (9 ¾" x 2") | Select side: | Left Hand Side | Right Hand Side | \$40 |
|----------------|--|----------------|-----------------------|--------------------|-------|
| SOGELF | Full Length Hybrid Gel and Foam Flat armpad – (13 ½" x 2") | Select side: | Left Hand Side | Right Hand Side | \$40 |
| SOXWGAP10 | X-Wide 3.5" (90 mm) Flat GEL Armpad, 10" (255 mm) Long | Select side: | Left Hand Side | Right Hand Side | \$95 |
| SOXWGAP14 | X-Wide 3.5" (90 mm) Flat GEL Armpad, 14" (355 mm) Long | Select side: | Left Hand Side | Right Hand Side | \$95 |
| SOXWGAP16 | X-Wide 3.5" (90 mm) Flat GEL Armpad, 16" (405 mm) Long | Select side: | Left Hand Side | Right Hand Side | \$105 |
| The V Wide 16" | v 2 1/" Armande require Cantilover (SOAEREvy) armres | te with an ovt | anded langth of 19" / | (AFF mm) or more | |

The X-Wide 16" x 3 1/2" Armpads require Cantilever (SOAFBExx) armrests with an extended length of 18" (455 mm) or more

The X-Wide 16" x 3 1/2" Armpads are NOT compatible with Dual Post Armrests (SOADPxx)

MKT.F70 | OF | PD-A20602 | R08







| SOWGEL | | | Length Hybrid Gel & Foam Waterfall armpa $\frac{1}{2}$ x 2 $\frac{3}{4}$ ") | d Select side: | Left Hand Side | | Right Hand Side | \$95 |
|--------------|----------|------------|---|------------------|---------------------------|----------|--------------------|---------|
| | | • | Z · · · = · · · ·) May interfere with flipping back the armrests w | | | k suppo | | |
| | | ▲ I | NOT compatible with Cantilever (SOAFBxxx) | | | | | |
| SOWGEL | _ | | ength Hybrid Gel and Foam Waterfall arm- (13" x 2 ¾") | Select side: | Left Hand Side | | Right Hand Side | \$95 |
| | | ▲ I | May interfere with flipping back the armrests w | hen combined w | ith Lateral Trun | k suppo | orts. | |
| | | | NOT compatible with Cantilever (SOAFBxxx) | | | | | |
| SPECIALT | Y TYP | E SE | LECTION | | | | | |
| SOCAR | | | Trough with Hand Support (18" x 4 ½") | Select side: | Left Hand Side | | Right Hand Side | \$290 |
| | | | Arm Trough Armpads may interfere with Armre | • | | | | |
| SOCAR ari | mpads | requi | ire Cantilever (SOAFBExx) armrests with an ex | tended length of | 18" (455 mm) o | r more | | |
| 0. SIGNATI | JRE T | AIL | ORED SOLUTIONS - FOOTRESTS | | | | | |
| SOSAAF | Sig | natur | e Swing-Away Footrests | | | | | STE |
| | | | Set at: | 60° | | 70° | | |
| | | | Select Footrest Range: | SOFLA12 (12 ½ | ' - 17 ½") | so | FLA14 (14 ½" – 19 | 9 ½") |
| SOAAF | Sig | natur | e Heavy Duty Swing-Away Footrests | | | | | \$175 |
| | | | Set at: | 60° | | 70° | | |
| | | | Select Footrest Range: | SOFLHD12 (12 | / ₂ " – 17 ½") | so | FLHD14 (14 ½" – | 19 ½") |
| ADDML | Sig | natur | e Manual Elevating & Articulating Legrests - | Pair | | | | \$595 |
| | | | Select Footrest Range: | SOFLME12 (12 | 1/2" – 17 1/2") | SO | FLME14 (14 ½" – | 19 ½") |
| | A | Doe | s not include calf pads. Please select calf pad | s in section 51. | | | | |
| ADDPL | Sig | natur | e Power Elevating & Articulating Legrests | | | | | \$2,495 |
| | | | Select Function: | ndividual | | Cor | mbined | |
| | | | Select Footrest Range: | SOFLPW12 (12 | 1/2" – 17 1/2") | so | FLPW14 (14 ½" – | 19 ½") |
| | A | | s option includes calf pads. Individual legs cou ction. | ınt as two power | functions. Com | bined le | egs count as one p | ower |
| 1. SIGNATI | JRE T | AIL | ORED SOLUTIONS - FOOTPLATES & | ACCESSORIE | s | | | |
| SOSFAF | Flip | -up F | ootplates | | | | | STE |
| SOAFP | Ang | gle A | djustable & Flip-up Footplates – (Each) | | | | | \$65 |
| SOAHL | He | el Loc | ops – (Each) | | | | | \$20 |
| SOACPF | R Cal | f Pac | ds for Adult Heavy-Duty Swing-Away footres | ts – (SOAAF) – v | with adjustable | hardwa | are – (Each) | \$93 |
| SOAMA | Sw | ing-a | way <mark>residual limb</mark> Support | Select: | Left leg | | Right leg | \$45 |
| 2. FOOTRE | ST LI | ENG | TH ADJUSTMENT AT FACTORY | | | | | |
| ➤ Set the Fo | | | wth at: " | | | | | |







| | | ILORED SOLUTIONS - CENTER MOUNTS | |
|---|----------------------------------|---|--|
| SOAAF90 | Fixed | d Center Mount Interface Bracket – (Offers Manual adjustability from 94° to 70°) | \$200 |
| | | Select Foot Platform Range: SOFBA12 (12 ½" – 16 ½") SOFBA16 (16 ½" – 19 | 9 1/2") |
| | • | When selecting SOFBA16 (16 $\frac{1}{2}$ " - 19 $\frac{1}{2}$ ") range, the lowest possible seat to floor height is 18.75" | |
| | • | Select the one piece center mount foot platform (SOFUFP) or the split footplates (SOAFPFB). | |
| | A | With the split footplates option (SOAFPFB), this bracket offers independent height adjustability for each | footplate. |
| ADDPF | 90° F | Power Center Mount Elevating & Articulating Foot Platform | \$2,49 |
| | | Select Footrest Range: SOFBPW12 (10 ½"- 16") SOFBPW16 (16"- 20" |) |
| | A | When selecting SOFBPW16 (16"- 20") range, the lowest possible seat to floor height is 18.75" | |
| | A | This option includes calf pads. The power center mount counts as one power function. | |
| | A | Select the one piece center mount foot platform (SOFUFP) or the split footplates (SOAFPFB). | |
| | A | For leg lengths between 10 $\frac{1}{2}$ " and 12 $\frac{1}{2}$ ", there is a partial conflict where the calf pads prevent the foot plates from folding completely. | |
| | A | The starting angle is reduced from 90° to 85° for some seat configurations when used with the narrow baconfiguration (FS2424B) | ise |
| | • | The E-BX (MAC) option is required with the combined selection of the 90° Power Center Mount Elevating lating Foot Platform (ADDPF) and the narrow base configuration (FS2424B) | & Articu- |
| 4. SIGNATUR | RE TA | ILORED SOLUTIONS - FOOT PLATFORMS & ACCESSORIES | |
| SOFUFP | Flip- | up one piece Foot Platform | \$140 |
| SOAFPFB | Angl | e Adjustable & Flip-up Split Footplates for center mount – (Each) | \$6 |
| SOACPCM | Calf | Pads for 90° Fixed Center Mount – (SOAAF90) with adjustable hardware – (Each) | \$93 |
| 5. FOOT PLA | TFOF | RM HEIGHT ADJUSTMENT AT FACTORY | |
| Set the Foo | t Plati | form Height at:" | |
| ▲ The Fo | oot Pla | tform Height is taken from the top of the seat pan to the top of the foot platform or split foot plates. | |
| 6. SEAT POS | OITI | NING | |
| SOAUTO | | 55" Seat Positioning Strap | |
| SOBPHP2C | | | STE |
| SOBFIIFZO | | Bodypoint padded Hip Belt – (Two Point – Center Pull) | |
| SOPHB | | Bodypoint padded Hip Belt – (Two Point – Center Pull) Padded Hip Belt. 2-PT Magnetic Center Pull | \$170 |
| SOPHB | | Padded Hip Belt, 2-PT Magnetic Center Pull | \$170 \$194 |
| SOPHB SOBPCS | | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap | \$17 \$19 \$25 |
| SOPHB SOBPCS SOPCS | | Padded Hip Belt, 2-PT Magnetic Center Pull | \$170 \$194 \$250 |
| SOPHB SOBPCS SOPCS 7. HEADRES | īΤ | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap | \$170 \$194 \$250 \$262 |
| SOPHB SOBPCS SOPCS 7. HEADRES | OF THE | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSUSTING headrest mounting hardware other than SOMAH below. | \$170 \$194 \$250 \$262 |
| SOPHB SOBPCS SOPCS 7. HEADRES SELECT ONE | 0F THI 12 A | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSULING Headrest mounting hardware other than SOMAH below. Isolable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts Ising headrest mounting hardware other than SOMAH below. | \$170 \$194 \$250 \$260 \$260 \$744 |
| SOPHB SOBPCS SOPCS 7. HEADRES SELECT ONE SONUAHR- | 0F THI 12 A 15 A | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSUSING headrest mounting hardware other than SOMAH below. Ivailable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts | \$170 \$194 \$250 \$262 STALLED. N/O |
| SOPHB SOBPCS SOPCS 7. HEADRES SELECT ONE SONUAHR- | 12 A 15 A | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSUSTING headrest mounting hardware other than SOMAH below. Invailable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts Ising headrest mounting hardware other than SOMAH below. Invailable with Reclining backrests only. 19/32 IN (15 MM) Mounts | \$170 \$194 \$250 \$262 \$74LLED. N/0 \$155 |
| SOPHB SOBPCS SOPCS 7. HEADRES SONUAHR- SONUAHR- SOFHRS | 0F THI 12 A 15 A M | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSULING Headrest mounting hardware other than SOMAH below. Invailable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts Ising headrest mounting hardware other than SOMAH below. Invailable with Reclining backrests only. 19/32 IN (15 MM) Mounts Ising headrest Pad – 4" x 9" Medium Curved Headrest Pad – 5" x 10" | \$170 \$194 \$250 \$262 STALLED. N/0 \$155 \$155 |
| SOPHB SOBPCS SOPCS 7. HEADRES SONUAHR- SONUAHR- SOFHRS SOFHRM | 12 A 15 A S | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSULING Headrest mounting hardware other than SOMAH below. Isolable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts Isolable with Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable with Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable with Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable with Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable with Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts Isolable With Reclining backrests only. 19/32 IN (15 MM) Mounts | \$170 \$194 \$250 \$262 \$74 \$750 \$150 \$150 \$150 \$150 |
| SOPHB SOBPCS SOPCS 7. HEADRES SONUAHR- SONUAHR- SOFHRS SOFHRM SOFHRL | OF THI 12 A 15 A S M | Padded Hip Belt, 2-PT Magnetic Center Pull Bodypoint padded Chest Strap Padded Chest Strap, 2-PT Magnetic Center Pull E HEADREST OPTIONS WITH THE MOUNTING HARDWARE AND SPECIFY WHERE THE HEADREST WILL BE INSULING Headrest mounting hardware other than SOMAH below. Invailable with both Fixed and Reclining backrests. 1/2 IN (12.7 MM) Mounts Ising headrest mounting hardware other than SOMAH below. Invailable with Reclining backrests only. 19/32 IN (15 MM) Mounts Ising headrest Pad – 4" x 9" Medium Curved Headrest Pad – 5" x 10" | \$170 \$194 \$250 \$262 \$744 \$156 \$156 \$156 \$220 \$770 \$770 \$770 \$770 \$770 \$770 \$770 |







| 58. | LATERAL TR | UNK S | SUPPORTS | | | | |
|----------|---------------|----------|--|-------------------|----------------------|-------------------|---------|
| V | | | LATERAL PADS AND THE ADJUSTABLE & REMOVA | ABLE HARDWA | ARE. | | |
| _ | SOSLS3 | | table Laterals with Small Curved Pads – (Each) – 3 | | W.L. | | \$100 |
| | SOSLM4 | - | table Laterals with Medium Curved Pads – (Each) - | | | | \$100 |
| | SOSLL5 | - | table Laterals with Large Curved Pads – (Each) – 5 | | | | \$100 |
| | SOSLHM | - | table Swing-Away Hardware Mounts – (Each) | | | | \$220 |
| | | A | The Lateral Trunk Supports are not compatible with Back Support (NOPCB). | the NXT Optima | a FH PC 6" Deep Co | ontour Fixed Tho | racic |
| | | A | Waterfall armpads (SOWAPx & SOWGELx) may inter Lateral Trunk supports | fere with flippii | ng back the armrest | s when combine | ed with |
| 59. | . HIP & THIGH | SUPP | ORTS | | | | |
| • | SELECT ONE O | F THE | HIP & THIGH SUPPORT PADS AND THE ADJUSTAB | LE & REMOVA | BLE HARDWARE. | | |
| | SOHTSS10 | Adjus | table Hip & Thigh Support Pads – (Each) – Small 1 | 0" x 4" | | | \$130 |
| | SOHTSM12 | Adjus | table Hip & Thigh Support Pads – (Each) – Medium | 12" x 5" | | | \$130 |
| | SOHTSL14 | Adjus | table Hip & Thigh Support Pads – (Each) – Large 1 | 4" x 6" | | | \$130 |
| | SOHTSARH | Adjus | table and Removable Hip & Thigh Support Hardwa | re – (Each) | | | \$136 |
| 60. | . ACCESSORII | ES | | | | | |
| | SOCH | Cup H | Holder – (Self-Leveling) | Install on: | Left Side | Right Side | \$115 |
| | SOCPH | Ram | Mounts X-Grip Cell Phone Holder | Install on: | Left Side | Right Side | \$190 |
| | SOTHS | Ram | Mounts X-Grip Small Tablet Holder | Install on: | Left Side | Right Side | \$205 |
| | SOTHL | Ram | Mounts X-Grip Large Tablet Holder with Swivel | Install on: | Left Side | Right Side | \$360 |
| | | | tandard installation is on the opposite side of joystick ay require a custom upgrade. | c. Installing acc | cessories on the sa | me side as the jo | ystick |
| | | ▲И | ith multiple accessories installed on the same side, a | custom upgra | de will be required. | | |
| 61. | REFLECTOR | KIT | | | | | |
| | REFLECT | Red 8 | White Reflector Kit Stickers (They will not be insta | illed – Included | l in a bag with the | Owner's Manua | al) N/C |
| 62. | BACK PACK | AND A | ARMREST SIDE POUCHES | | | | |
| | SOBP | Back | Pack – (Comes with durable straps that can be hoo | ked around th | e back canes) | | \$90 |
| | SOAP | | est Side Pouch – (Comes with durable straps that ced around the armrest tubes) | an be | Order: Left Side | Right Side | \$53 |
| | | A | If only choosing one (1) armrest pouch, please show | what side it sho | ould be installed | | |
| 63. | . SWITCHES A | ND OI | PTIONS | | | | |
| | ASCPWIFI | PGD | Г - Wireless programmer, WIFI dongle | | | | \$844 |
| | ASCPCP | | R-NET Dongle and PC programmer kit | | | | \$600 |
| | ASCPVR2 | PGD | Г VR2 with PPI Dongle and PC programmer kit | | | | \$1,450 |
| | SSBS | | y Button Switch | | | | \$230 |
| | SSES | | Switch-Black | | | | \$116 |
| | SSML | Ultra | Light Switch | | | | \$295 |
| | ESS-RED | Emer | gency STOP Switch - Red | | | | \$314 |







SPECIALTY DRIVER CONTROL OPTIONS

▶ Specialty Drive Control options all require the Omni 2 Enhanced Display & Digital Interface Box (EDIB)

| | | · · · | | · , | |
|-----|------------|---|--------------------------------|-----------------------|---------|
| 64. | THERAFIN | SIP-N-PUFF KIT | | | |
| | SCSNPK | Therafin Sip-N-Puff Kit | | | \$1,975 |
| | SCSNPBTK | Therafin Sip-N-Puff Breath Tube Kit | | | N/C |
| | | ▲ Required with the Therafin Sip-N-Puff kit. | | | |
| | SCSRMSNP | Stealth Rock-n-Lock Swingaway Arm for Sip-N-Puff | SWL (Swings on Left) | SWR (Swings on Right) | \$300 |
| | | ▲ Required with the Therafin Sip-N-Puff kit. | | | |
| | SCSRM | Stealth Rock-n-Lock Swingaway Mount for Mode Switch | SWL (Swings on Left) | SWR (Swings on Right) | \$510 |
| | SSES | Egg Switch for Changing Modes – Black | MLH (Mount on Left) | MRH (Mount on Right) | \$116 |
| | | ▲ Required with the Stealth Rock-n-Lock Swin | g Away mount. | | |
| | | ▲ The Mode Switch Type can be changed from | this selection in SWITCHES & O | PTIONS section | |
| | ESS-RED | Emergency STOP Switch - Red | User Activation | Attendant Activation | \$314 |
| | | ▲ Required with the Therafin Sip-N-Puff kit. | | | |
| | SOMAH | Multi-axis Headrest Removable Mounting Hard | ware | | \$220 |
| | | ▲ Required with the Therafin Sip-N-Puff kit. | | | |
| • | CHOOSE ONE | E (1) HEADREST PAD | | | |
| | SOFHRS | Small Curved Headrest Pad – 4" x 9" | | | \$155 |
| | SOFHRM | Medium Curved Headrest Pad – 5" x 10" | | | \$155 |
| | SOFHRL | Large Curved Headrest Pad – 6" x 11" | | | \$155 |
| 65. | PROXIMITY | HEAD ARRAY | | | |
| | SCSIHAA | Adult - Switch-It 3 Switch Proximity Head Array | with 1/8" Mono Jack for mode/ | reverse | \$5,995 |
| | SCSRM | Stealth Rock-n-Lock Swingaway Mount for Mode Switch | SWL (Swings on Left) | SWR (Swings on Right) | \$510 |
| | SSES | Egg Switch for Changing Modes – Black | MLH (Mount on Left) | MRH (Mount on Right) | \$116 |
| | | ▲ Required with the Stealth Rock-n-Lock Swin | g Away mount. | | |
| | | ▲ The Mode Switch Type can be changed from | this selection in SWITCHES & O | PTIONS section. | |
| | ESS-RED | Emergency STOP Switch - Red | User Activation | Attendant Activation | \$314 |
| | | ▲ Required with the Proximity Head Array. | | | |
| | SOMAH | Multi-axis Headrest Removable Mounting Hard | ware | | \$220 |
| | | ▲ Required with the Proximity Head Array. | | | |
| 66. | LIGHT TOU | CH PROPORTIONAL MINI JOYSTICK FO | R CHIN / LIP CONTROL | | |
| | SCSIMP | Switch-It Light touch mini Proportional Joystick | | | \$4,495 |
| | SCSRMMP | Stealth Rock-n-Lock Swingaway Arm for Chin MF | SWL (Swings on Left) | SWR (Swings on Right) | \$870 |
| | | ▲ Required with the Light touch mini Proportion | , - | , , | |
| | SCSRM | Stealth Rock-n-Lock Swingaway Mount for Mode Switch | SWL (Swings on Left) | SWR (Swings on Right) | \$510 |
| | SSES | Egg Switch for Changing Modes – Black | MLH (Mount on Left) | MRH (Mount on Right) | \$116 |
| | | ▲ Required with the Stealth Rock-n-Lock Swin | , | | |
| | | ▲ The Mode Switch Type can be changed from | | PTIONS section | |
| | JCC | Chin Cup | | | \$55 |
| | | | | | |

MKT.F70 | OF | PD-A20602 | R08









| 66. | LIGHT TOU | CH PROPORTIONAL MINI JOYSTICK FOR CHIN / LIP CONTROL (CONTINUED) | | | | | | |
|----------|------------|---|---------|--|--|--|--|--|
| | SOMAH | Multi-axis Headrest Removable Mounting Hardware | \$220 | | | | | |
| | | Required with the Light touch mini Proportional Joystick. | | | | | | |
| • | CHOOSE ONE | (1) HEADREST PAD | | | | | | |
| | SOFHRS | Small Curved Headrest Pad – 4" x 9" | \$155 | | | | | |
| | SOFHRM | Medium Curved Headrest Pad – 5" x 10" | \$155 | | | | | |
| | SOFHRL | Large Curved Headrest Pad – 6" x 11" | \$155 | | | | | |
| 67. | PROPORTIO | ONAL COMPACT OR MINI JOYSTICK FOR MIDLINE MOUNT | | | | | | |
| | SCPGMJS | PG Drives JC200 Proportional Compact Remote Joystick for Midline Mount | \$2,369 | | | | | |
| | SCGMJSM | Gatlin Midline Swing-away Mount for JC200 MLH (Mount on Left) MRH (Mount on Right) | | | | | | |
| | | ▲ Must be selected for use with the PG Drives JC200 Mini Joystick. | | | | | | |
| | SCSIMP | Switch-It Light touch mini Proportional Joystick | \$4,495 | | | | | |
| | SCGMPM | Gatlin Midline Swing-away Mount for Light touch mini proportional Joystick MLH (Mount on Left) MRH (Mount on Right) | \$750 | | | | | |
| | | ▲ Must be selected for use with the Light touch mini Proportional Joystick. | | | | | | |
| | SCBTM | Bullet Hand Tray for Light Touch mini Proportional Joystick MLH (Mount on Left) MRH (Mount on Right) | \$750 | | | | | |
| | | ▲ This option is only compatible with the Light touch Mini Proportional Joystick. | | | | | | |
| 68. | PROPORTIO | ONAL COMPACT OR MINI JOYSTICK FOR ARMREST MOUNT | | | | | | |
| | SCPGMJS-M | PG Drives JC200 Proportional Compact Remote Joystick for Armrest Mount | \$2,369 | | | | | |
| | SCARMJSM | Swing-away and Multi-Axis armrest mount MLH (Mount on Left) MRH (Mount on Right) | \$325 | | | | | |
| | | ■ Must be selected for use with the PG Drives JC200 Mini Joystick. | | | | | | |
| | SCSIMP | Switch-It Light touch mini Proportional Joystick | \$4,495 | | | | | |
| | SCARMPM | Swing-away and Multi-Axis armrest mount MLH (Mount on Left) MRH (Mount on Right) | \$375 | | | | | |
| | | ■ Must be selected for use with the Light touch mini Proportional Joystick. | | | | | | |
| | SCBTM | Bullet Hand Tray for Light Touch mini Proportional Joystick MLH (Mount on Left) MRH (Mount on Right) | \$750 | | | | | |
| | | ▲ This option is only compatible with the Light touch Mini Proportional Joystick. | | | | | | |
| 69. | PROPORTIO | ONAL RIM HEAD CONTROL PACKAGE | | | | | | |
| | SCPHC | Proportional RIM Head Control Package | \$2,795 | | | | | |
| | SCSRM | Stealth Rock-n-Lock Swingaway Mount for Mode Switch SWL (Swings on Left) SWR (Swings on Right) | \$510 | | | | | |
| | SSES | Egg Switch for Changing Modes – Black MLH (Mount on Left) MRH (Mount on Right) | \$116 | | | | | |
| | | ▲ Required with the Stealth Rock-n-Lock Swing Away mount. | | | | | | |
| | | ▲ The Mode Switch Type can be changed from this selection in SWITCHES & OPTIONS section | | | | | | |
| | SOMAH | Multi-axis Headrest Removable Mounting Hardware | \$220 | | | | | |
| | | ▲ Required with the Proportional RIM Head Control. | | | | | | |







CUSTOM SECTION

- Lead times will increase depending on the custom order pipeline at the time the purchase order is received.
- ▶ Please call for Quote and specifications for these options.

| _ | _ | | _ | 2 | | | | _ | _ | |
|---|---|---|---|----|---|---|---|---|---|---|
| | п | | | 14 | = | 0 | | | | ~ |
| | u | _ | v | | | | _ | _ | _ | |

| SUPOXY | Cus | tom Non-A | Articulating Oxygen Tank Holder | MLH (Mount on Left) | MRH (Mount on Right) | \$295 | | |
|---------|----------|------------|------------------------------------|--|----------------------|---------|--|--|
| | A | Not avail | able with a power recline | | | | | |
| SUPOXYA | Cus | tom Articu | lating Oxygen Tank Holder | MLH (Mount on Left) | MRH (Mount on Right) | \$1,195 | | |
| | A | Required | l with a power recline | | | | | |
| | | D-Size | Oxygen Tank – (* 22" Tall x 4.3" I | exygen Tank – (* 22" Tall x 4.3" Diameter) – * The height includes the valve | | | | |
| | | E-Size | Oxygen Tank – (* 31" Tall x 4.3" I | xygen Tank – (* 31" Tall x 4.3" Diameter) – * The height includes the valve | | | | |

71. VENT TRAY (PLEASE COMPLETE IN FULL)

▼ AMYLIOR DOES NOT SUPPLY THE BATTERY, CHARGER OR THE WIRING FOR THE VENT. THESE ITEMS ARE NORMALLY PROVIDED BY THE VENT MANUFACTURER.

| SOVENT | Cus | stom Vent Tray | | | | | | |
|--------|------|---|---------|--|--|--|--|--|
| | | Articulating Vent Box (Required with Power Tilt and/or Recline) | \$1,360 | | | | | |
| | | Fixed Vent Box | \$400 | | | | | |
| | SPE | ECIFY MODEL | | | | | | |
| | | Trilogy 100/200 | | | | | | |
| | | LTV | | | | | | |
| | | LTV with Sprintpack | | | | | | |
| | | Other, specify: | | | | | | |
| SOVTBE | Exte | ended Battery Compartment | \$495 | | | | | |
| | • | The Vent Tray option is not available on narrow options N2424 & N2221 (FS2424B & FS2221B) | | | | | | |
| | | The Vent is being powered by 1 U1 Battery and the chair by 2 Group 22NF batteries | | | | | | |
| | | The Vent is being powered by 1 U1 Battery and the chair by 2 Group 24 batteries | | | | | | |
| | | The Vent is being powered by 1 Group 22NF Battery and the chair Powered by 2 Group 22NF Batter | ries | | | | | |
| | | The Vent is being powered by 1 Group 24 Battery and the chair Powered by 2 Group 22NF Batteries | | | | | | |
| | | The Vent is being powered by 1 Group 22NF Battery and the chair Powered by 2 Group 24 batteries | | | | | | |







72. OTHER CUSTOM OPTIONS (REQUEST FOR QUOTE)

▼ PLEASE SPECIFY DETAILS AND SPECIFICATIONS FOR THESE OPTIONS.

| OUOTOM | OLIOTO | NA 1 :41-: | | A / | | / D | -44 | | -141 | 0 | |) D - 44) | DEC |
|-----------|--|-------------|-----------|---------------|--------------------|--------------------------|-----------------------|---------------------------|----------|----------------------------|-----|------------|-----|
| CUSTOM | | | | | | | | | | | RFQ | | |
| CUSTOM | | | | | | | | | | | RFQ | | |
| CUSTOM | CUSTOM 8A Offboard Battery Charger for Lithium ion batteries | | | | | | | | | | N/C | | |
| | ▲ Thi | s option is | required | when choo | sing custom Lit | hiun | n ion batteri | es | | | | | |
| CUSTOM | CUSTOM Lithium ion Battery capacity LCD display gauge | | | | | | | | | | | N/C | |
| | ▲ Thi | s option is | required | when choo | sing custom Lit | hiun | n ion batterie | es | | | | | |
| CUSTOM | Rear view Camera with 5" Monitor | | | | | | | | | | | RFQ | |
| CUSTOM | USB Charger Port ◀ Specify the location for the installation: | | | | | | | | | | RFQ | | |
| CUSTOM | Folding Backrest for Storage/Travel Access for Reclining backs | | | | | | | | | | RFQ | | |
| CUSTOM | Large Ball Handle | | | | | | | | | | RFQ | | |
| CUSTOM | Tilt + Elevate Function Through VR2 Non-Expandable Drive Control | | | | | | | | | | RFQ | | |
| CUSTOM | Manual Wheel Locks | | | | | | | | | | RFQ | | |
| CUSTOM | Power Anterior Tilt | | | | | | | | | | RFQ | | |
| CUSTOM | Power Lateral Tilt 15° | | | Raise Side | e the Left only | Raise the Righ Side only | | ght Raise the Let Side | | ft & Right | RFQ | | |
| CUSTOM | Power Latitude System (Features 14" of forward travel and a 5" seat to floor height from the pan to the ground) (200 Lb max. user weight capacity) | | | | | | | | | | RFQ | | |
| CUSTOM | Power Elevating Stretcher – (Please call CSR for availability with configuration and user weight capacity) | | | | | | | | | | RFQ | | |
| CUSTOM | Power Flip-up Foot Platform – (Please call CSR for availability with configuration and user weight capacity) | | | | | | | | | | RFQ | | |
| CUSTOM | Power Vertical Lifting Foot Platform – (Please call CSR for availability with configuration and user weight capacity) | | | | | | | | | | | RFQ | |
| CUSTOM | Rearview mirror Left Side Right Side | | | | | | | | RFQ | | | | |
| CUSTOM | Independent Depth Adjustability built into the Footrest Receiver that is attached to the Seat Pan RF | | | | | | | | | | | | RFQ |
| CUSTOM | Transfe | r Handles | – (Pair) | Select a | height range: | | 5" to 8" | (| 6" to 9" | | | | RFQ |
| CUSTOM | Foot ◀ Length: | | | Width: | | | Please confirm with C | | ith CSF | SR on sizing possibilities | | | RFQ |
| CUSTOM | Access | ory Hooks | located a | at the Rea | of the seat stru | ıctu | re | | 2 Ho | oks | | 4 Hooks | RFQ |
| CUSTOM | Heavy-Duty Wheelchair Cover, Large | | | | | | | | | | | RFQ | |
| CUSTOM #1 | Other custom options. Specify in notes section below | | | | | | | | | | | RFQ | |
| CUSTOM #2 | Other custom options. Specify in notes section below | | | | | | | | | | RFQ | | |









| 73. NOTES / SPECIAL REQUESTS / CUSTOM SPECIFICATIONS |
|--|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |